



Revised: September 2017

MAINTENANCE GUIDE

Product Range:	PTP15/15 ISF and PTP15/15 OSF	
	Materials	uPVC Compound
General:	<p>The installed profile should be swept clean on a daily basis to avoid build up of dust and dirt which may make it more difficult to maintain its appearance. Immediately after installation and the removal of protective tape, the flooring profile should be wiped with a dry, soft cloth to remove any handling marks and fingerprints.</p> <p>PTP15/15 profiles are available in Black, Light Grey, White.</p>	
Cleaning:	<p>PTP15/15 finishes can be cleaned using soap and warm water. Sponge the soiled area with the solution, then rinse with clean water and dry. Do not use strong chemical cleaners as this may lead to the deterioration of the uPVC.</p>	
Important:	<p>Ensure that all surfaces are wiped dry after cleaning before allowing pedestrian access.</p> <p>Care must be taken to protect surrounding floor finishes during maintenance.</p>	

C.A.T. LTD. Units 24A,B,C Park Avenue Estate, Luton Bedfordshire LU3 3BP. U.K.

T: +44 (0) 1582 561500 F: +44 (0) 1582 561900

email: sales@cat-accs.com

website: www.thecatweb.com

Manufacturers Of The Finest Specialist Flooring Accessories
www.thecatweb.com