



## PRODUCT TECHNICAL DATA SHEET

Revised: October 2021

**Catalogue Reference:**

**OLYMPIC SS256**

**Uniclass2015:**

**Pr\_35\_90\_31\_84 STAIR TRIMS**

**General Description:**

**STAINLESS STEEL STAIR INSERT WITH SLIP RESISTANT CARBORUNDUM INFILL**

Folded Profile- Single Channel

Infill colour options & LRV's

Black 4.76  
Yellow 47.07  
White 58.45



Olympic Carborundum SRVs: PTV Dry - 92 PTV Wet - 86

**Specifications:**

Material	Stainless Steel Grade 304L
Tread Dimension	25mm
Nosing Dimension	n/a
Gauge	6.5mm
Lengths available	Cut to customer sizes up to 2000mm
Finishes available	Mill Finish LRV 71.65
Fixing	Adhesive. We recommend Stycco Flex rapid curing flexible adhesive by F. Ball & Co Ltd. subject to following their instructions for use.

**Application:**

For rebating into stone and wooden steps or between ceramic tiles, to provide a visual aid and slip resistance.  
Suitable for exterior and interior wet environments.  
Installation guide available.

**Suitability:**

Very heavy foot traffic situations such as in hotels, pubs, clubs, cafes, shops, schools, commercial offices and apartment buildings.

C.A.T. LTD. Units 24A,B,C Park Avenue Estate, Luton Bedfordshire LU3 3BP. U.K.

T: +44 (0) 1582 561500 F: +44 (0) 1582 561900

email: [sales@cat-accs.com](mailto:sales@cat-accs.com)

website: [www.thecatweb.com](http://www.thecatweb.com)

**Manufacturers Of The Finest Specialist Flooring Accessories**  
**[www.thecatweb.com](http://www.thecatweb.com)**