



Revised: September 2017

## MAINTENANCE GUIDE

<b>Product Range:</b>	<b>KKSL25 - KLIKS SLIM ALUMINIUM TWIN TOP WITH BONDED BRUSHED STAINLESS STEEL COVER</b>	
	Materials	Base profile: Aluminium Alloy 6063 T6 Bonded Cover: Grade: 304L Stainless Steel
<b>General:</b>	<p>The installed profile should be swept clean on a daily basis to avoid build up of dust and dirt which may make it more difficult to maintain its appearance. Immediately after installation and the removal of protective tape, the flooring profile should be wiped with a dry, soft cloth to remove any handling marks and fingerprints.</p> <p>KKSL235 is produce with a brushed stainless steel finish.</p>	
<b>Cleaning:</b>	<p>Stainless steel profiles generally need little maintenance but heavy soiling can be cleaned using soap, ammonial or detergent and warm water. Sponge the soiled area with the solution, then rinse with clean water and dry. Goddards Stainless Steel Care may be used for stubborn stains. Always follow the manufacturer's instructions for use.</p> <p>Prolonged exposure to damp environments, acids or strong alkali solutions may lead to corrosion of the metal.</p>	
<b>Important:</b>	<p><b>Ensure that all surfaces are wiped dry after cleaning before allowing pedestrian access.</b></p> <p><b>Care must be taken to protect surrounding floor finishes during maintenance.</b></p>	

C.A.T. LTD. Units 24A,B,C Park Avenue Estate, Luton Bedfordshire LU3 3BP. U.K.

T: +44 (0) 1582 561500 F: +44 (0) 1582 561900

email: sales@cat-accs.com

website: www.thecatweb.com

**Manufacturers Of The Finest Specialist Flooring Accessories**  
**www.thecatweb.com**