



Revised: October 2018

MAINTENANCE GUIDE

Product Range:	KLIKS SLIM ALUMINIUM END STOP - SATIN FINISH WITH EXPANSION MEDIUM		
	<table border="1"><tr><td>Materials</td><td>Base profile: Aluminium Alloy 6063 T6 Expansion Medium: Flexible PVC/Nitrile to BSS86/Shore hardness A57, opaque with colour additive</td></tr></table>	Materials	Base profile: Aluminium Alloy 6063 T6 Expansion Medium: Flexible PVC/Nitrile to BSS86/Shore hardness A57, opaque with colour additive
Materials	Base profile: Aluminium Alloy 6063 T6 Expansion Medium: Flexible PVC/Nitrile to BSS86/Shore hardness A57, opaque with colour additive		
General:	The installed profiles should be swept clean on a daily basis to avoid build up of dust and dirt which may make it more difficult to maintain its appearance. Immediately after installation and the removal of protective tape, the profiles should be wiped with a dry, soft cloth to remove any handling marks and fingerprints.		
Cleaning:	Aluminium profile: Wipe clean with a mild detergent, diluted with water, on a damp, not wet, cloth. To remove scuffs and small scratches, a green or red Scotch pad can be used, rubbing along the grain of the existing finish. Expansion medium: Wipe clean with a mild detergent, diluted with water, on a damp, not wet, cloth. For heavier soiling, use *Stycco-Wipes.		
Important:	Ensure that all surfaces are wiped dry after cleaning before allowing pedestrian access. Care must be taken to protect surrounding floor finishes during maintenance.		

*Stycco-Wipes are specially formulated to remove adhesive, sealants, oil, grease, lacquer, tar bitumen, wet paint and more from hands and tools.

Stycco-Wipes enhanced anti-bacterial formulation easily removes bacteria from hands and tools. Effective against MRSA, Salmonella, Listeria and E.Coli. Tested by independent laboratory to BS EN 12054 and BS 1276 standards.

Note •Do not use on porous surfaces such as untreated wood

•On sensitive surfaces test on a small inconspicuous area before use

•Use only as directed

•It is the user's responsibility to determine suitability for use

•DO NOT FLUSH

•If in doubt please contact F. Ball's Technical Department on 01538 361 633

C.A.T. LTD. Units 24A,B,C Park Avenue Estate, Luton Bedfordshire LU3 3BP. U.K.

T: +44 (0) 1582 561500 F: +44 (0) 1582 561900

email: sales@cat-accs.com

website: www.thecatweb.com

Manufacturers Of The Finest Specialist Flooring Accessories
www.thecatweb.com