

## PRODUCT TECHNICAL DATA SHEET

Revised: October 2021

Catalogue Reference:

**OLYMPIC 551** 

Uniclass2015:

Pr\_35\_90\_31\_74 RIGID STAIR NOSINGS

**General Description:** 


ALUMINIUM STAIR NOSING WITH CARBORUNDUM INFILL

Single Channel/Square Front.

Colour matched riser inserts to aid those with visual impairment (Equality Act 2010)

Infill colour options & LRV's: Black LRV 4.76 Yellow LRV 47.07 White LRV 58.45

SRVs: PTV Dry - 92 PTV Wet - 86



**Specifications:** 

Material	Aluminium Alloy 6063 T6
Tread Dimension	55mm
Nosing Dimension	55mm
Gauge	7mm
Lengths available	Cut to customer sizes up to 2500mm
Finishes available & LRV's	Mill Aluminium Avg. LRV 71.65
Drilling	Can be supplied pre-drilled and countersunk through the aluminium rib. Screw heads remain visible when installed. Drilled for size 8 screws. Fixings not supplied.

**Application:** 

For abutting to floor coverings of equal thickness to finish the nose edge of stairs.

Can be rebated to sit flush in wooden steps.

Compatible with profiles: Olympic 78, Olympic 35. Installation guide available.

Suitability:

Exterior and wet environments and very heavy foot traffic situations such as in hotels, pubs, clubs, cafes, shops, schools, commercial offices and apartment buildings.

C.A.T. LTD. Units 24A,B,C Park Avenue Estate, Luton Bedfordshire LU3 3BP. U.K.

T: +44 (0) 1582 561500 F: +44 (0) 1582 561900 email: sales@cat-accs.com website: www.thecatweb.com