

Catalogue Reference:

PRODUCT TECHNICAL DATA SHEET

Uniclass2015:

Pr_35_90_31_74 RIGID STAIR NOSINGS

General Description:

BRASS STAIR NOSING WITH RAMPED BACK EDGE AND SLIP RESISTANT OLYMPIC GRIP INFILL Single Channel/Round Front. Supplied with Olympic Grip carborundum Infill.

Infill Colour Options & LRV's:

Olympic Black LRV: 4.85

BN14



Revised: Oct 2021

Olympic Grip Infill SRVs: PTV Dry - 92 PTV Wet - 86

Specifications:

Material	Solid Brass Grade H/H CZ108 BS EN 12164:2016
Tread Dimension	63.5mm
Nosing Dimension	30mm
Gauge	3.5mm ramping down to 0.5mm
Lengths available	Cut to customer sizes up to 3200mm
Finishes available & Associated Light Reflective Values or LRV's	Polished Brass Avg. LRV 71.45 Satin Brass Avg. LRV 59.55 Antique Brass Avg. LRV 29.55 Antique Bronze Avg. LRV 9.15 Antique Brass and Antique Bronze finishes are a chemically applied process and are hand finished with a variance from batch to batch. They are not foot-traffic resistant and are designed to create an aged, unpolished effect.
Drilling	Can be supplied undrilled or pre-drilled and countersunk in the channel for concealed fixing and on-site retro fitting of the infill. Drilled for size 6 screws. Fixings not supplied.

Application:

To finish the nose edge of stone and timber stairs and stairs fitted with ceramics and hard flooring, e.g. laminates, LVT, vinyl, lino.

Suitability:

Heavy foot traffic such as in hotels, pubs, clubs, cafes, shops, schools, commercial offices and apartment buildings.

Additional Information:

Also available with Castellated/Smooth Textured PVC infill and BTI49.5 tread insert for an all-brass installation.

Post Consumer Recyclability: This product is 100% recyclable at suitable disposal centres.

C.A.T. LTD. Units 24A,B,C Park Avenue Estate, Luton Bedfordshire LU3 3BP. U.K.

T: +44 (0) 1582 561500 F: +44 (0) 1582 561900 email: sales@cat-accs.com website: www.thecatweb.com

Manufacturers Of The Finest Specialist Flooring Accessories www.thecatweb.com